

Frame & Roof











Frame Colors (Poli-5000 ® Certified)

The most durable frame finish available in the industry.

The Poli-5000[®] Super-Durable TGIC powder coat offers excellent outdoor durability and fade resistance to our steel shelter frames. It is tough, resilient, and will withstand harsh environments while retaining its smooth, high-gloss or matte finish for years to come.



*represents frame colors also available in matte finish **represents frame colors available with a slight upcharge

Due to the nature of printed materials, colors may vary slightly from the swatches shown. Please request actual color sample before making final selection.

Roof Colors (Kynar-500® Certified)

Providing protection against weathering to extend the life of your roof.

Kynar-500[®] PVDF resin-based coatings offer excellent protection to our metal roofs. The high-performance fluoropolymer resin, with its extraordinary capability to retain color and gloss, keeps your painted metal roof looking vibrant and appealing.



*represents roof colors available with a slight upcharge

The underside of MR and SS roof is white prime paint

Due to the nature of printed materials, colors may vary slightly from the swatches shown.

Please request actual color sample before making final selection.

Frame & Roof Finish Technical Data



We are certified by the Powder Coating Institute as PCI-4000. This means that we ensure all of our products are produced with a high quality powder coated frame. As a certified coater, we have developed a methodology to continually improve and enhance our power coating process, giving you the best product available on the market.

Poli-5000[®] Durability & Longevity Testing

Test Description	Test Method	Poli-5000® Results
Salt Spray Resistance	ASTM B 117 / ASTM D 1654 Method 2 (No scraping)	10,000 hours, no creep from scribe line, rating of 10
Humidity	ASTM D2247-02	5,000 hours with no loss of adhesion or blistering
UV Light Resistance	ASTM G154-04 - 2,000 hours of exposure. Alternate cycles (4 hours UVA and 4 hours condensation)	 A) No chalking B) 75% color retention C) Color variation - max 3.0 E variation CIE formula (before and after 2,000 hours of exposure)
Stain Resistance	ASTM D1308 - 2e1 24 hours exposure with 10% concentration	No stain from the following: Mustard, Tannic Acid, Ketchup, Citric Acid, Coffee, Tartaric Acid, Cola, Oleic Acid, Lactic Acid, Orange Juice
Scratch Resistance	Hoffman Scratch Hardness Tester	No substrate appearance with 1,000 gram load
Adhesion	ASTM D3359-02	ASTM Class 4B rating or better
Impact Resistance	ASTM D2794-93	100 in lbs. without cracking
Hardness	ASTM D6636-92a	2H min no indentation
Flexibility	ASTM D522-93a	1/8" no cracking or loss of adhesion at bend
Abrasion	Taber abraser CS10 Wheel (1,000 mg. load)	14 mg. max weight loss per cycle
Solvent Resistance	50+ MEK rubs	Minimal to no dulling or color removal

Poli-5000[®] Frame Finish

Excellent Durability

- Higher surface hardness / scratch resistance
- Reduced chance of damage to coating during installation
- High resistance to cleaners and chemicals
- High resistance to wind borne abrasives
- Superior Exterior Performance
- High resistance to salt spray
- High resistance to chalking
- High resistance to film coating erosion
- Excellent color and gloss retention

Connect with Poligon

Kynar-500[®] Roof Finish

This high-performance fluoropolymer resin withstands the rigors of nature and time with its extraordinary capability to retain color and gloss. Noted by architects around the world, our Kynar-500[®] coated roofs will keep your shelter looking its best for years to come.

Technical Notes

Custom colors are available for frames and roofs. Such colors may incur an up charge, require extended lead times, and have minimum order requirements. Custom roof colors may not be Kynar-500[®]. Consult with Poligon for details.

Our knowledgeable sales staff will answer your questions, forward materials, or refer you to a representative in your area.

